

CLAIMS

1. A method of treating a tumor comprising:

- 5 providing a tissue biopsy and treatment apparatus for detecting and treating a tumor, the apparatus comprising an elongated delivery device including a lumen, the elongated delivery device being maneuverable in tissue; a sensor array deployable from the elongated member, the sensor array including a plurality of resilient members, at least one of the plurality
- 10 of resilient members being positionable in the elongated delivery device in a compacted state and deployable with curvature into tissue from the elongated delivery device in a deployed state, at least one of the plurality of resilient members including at least one of a sensor, a tissue piercing distal end or a lumen, the sensor array having a geometric configuration adapted to volumetrically sample tissue at a tissue site to differentiate or identify
- 15 tissue at the tissue site; and at least one energy delivery device coupled to one of the sensor array, at least one of the plurality of resilient members or the elongated delivery device;
- 20 introducing the apparatus into a target tissue site;
- distinguishing a tissue type utilizing the sensor array;
- positioning the energy delivery device utilizing tissue type information derived from the sensor array to ablate a tumor volume;
- delivering energy from the energy delivery device to ablate or necrose at least a portion of the tumor volume; and
- 25 determining an amount of tumor volume ablation utilizing the sensor array.

2. The method of claim 1, further comprising:

monitoring a tissue volume in the target tissue site.

3. The method of claim 2, wherein the apparatus includes logic resources coupled to at least one of the sensor, the energy delivery device or a power source coupled to the energy delivery device, the method further comprising:

adjusting one of a power, current, power duty cycle or fluid flow response to an input from the sensor array.

4. The method of claim 3, wherein the input is at least one of a temperature, an impedance, an optical absorbance, an optical reflectance or a pH.

5. The method of claim 3, wherein the logic resources include at least one of a processor, a microprocessor, a software module, a fuzzy logic module, a temperature compensation module, or a database.

6. The method of claim 2, wherein the tissue volume includes at least a first tissue volume and a second tissue volume.

7. The method of claim 6, wherein the at least a first tissue volume is in closer proximity to the energy delivery device than the second tissue volume.

8. The method of claim 6, wherein the first tissue volume is within a tumor volume and the second tissue volume is outside of the tumor volume.

9. The method of claim 1, further comprising:
comparing a first tissue volume to a second tissue volume.

5 10. The method of claim 9, wherein the first tissue volume is in substantial proximity to a first portion of the sensor array and the second tissue volume is in substantial proximity to a second portion of the sensor array.

10 11. The method of claim 10, further comprising:
positioning the first portion of the sensor array in the first tissue volume and the second portion of the sensor array in the second tissue volume.

15 12. The method of claim 9, further comprising:
comparing a property of the first tissue volume to a property of the second tissue volume.

20 13. The method of claim 13, wherein the tissue property includes at least one of a physiologic property, a metabolic property, a genetic property, a thermal property, a temperature, an electrical property, an impedance, an optical property, an absorbance, a reflectance, a dimensional property or a pH.

25 14. The method of claim 9, wherein the first tissue volume is within a tumor volume and the second tissue volume is outside of the tumor volume.

15. The method of claim 9, further comprising
differentiating between a first tissue type in the first tissue volume and a second tissue type in the second tissue volume.

16. The method of claim 10, wherein at least the first sensor array portion is positioned in closer proximity to the energy delivery device than the second sensor array portion.

5 17. The method of claim 10, wherein at least the first sensor array portion includes a first plurality of sensors and the second sensor array portion includes a second plurality of sensors.

10 18. The method of claim 1, further comprising:
locating a tumor volume within the target tissue site utilizing the sensor array.

15 19. The method of claim 18, further comprising:
positioning the sensor array to detect one of the tumor volume or a boundary of the tumor volume.

20 20. The method of claim 18, further comprising:
positioning the energy delivery device within the located tumor volume to controllably ablate at least a portion of the target volume.

21. The method of claim 1, further comprising:
identifying a tumor boundary utilizing the sensor array.

25 22. The method of claim 21, further comprising:
positioning the energy delivery device relative to the tumor boundary to controllably ablate at least a portion of a tumor volume.

23. The method of claim 1, further comprising:

determining an amount of tissue necrosis, coagulation, or injury
utilizing the sensor array.

5 24. The method of claim 1, further comprising:
determining a treatment end point utilizing the sensor array.

 25. The method of claim 1, further comprising
determining a healthy tissue ablative margin responsive to an input
from the sensor array.

10 26. The method of claim 25, wherein the input is at least one of
an optical input, a spectra, an absorbance spectra, a reflectance spectra, a
change in reflectance, a change in absorbance, a tissue type or a tissue
property.

15 27. The method of claim 25, further comprising:
positioning the energy delivery device within the a tissue volume
defined by the healthy tissue margin;
delivering energy from the energy delivery device to ablate or
20 necrose tissue in the tissue volume defined by the health tissue margin.

 28. The method of claim 25, wherein the healthy tissue margin is
determined using logic resources coupled to the sensor array.

25 29. The method of claim 25, wherein the logic resources are
electronically coupled to a power source coupled to the energy delivery
device.

30. The method of claim 25, wherein the logic resources include at least one of a processor, a microprocessor, a software module, a fuzzy logic module, a database, a histological database, a tumor database, or a database of prior ablations.

5

31. The method of claim 30, further comprising:
comparing an input from the sensor array to the database.

32. The method of claim 1, further comprising:
10 identifying at least one of a tissue type or a tissue property utilizing the sensor array.

33. The method of claim 32, wherein the tissue identification is determined using logic resources coupled to the sensor array.

15

34. The method of claim 33, wherein the logic resources are electronically coupled to a power source coupled to the energy delivery device.

35. The method of claim 33, wherein the logic resources include at least one of a processor, a microprocessor, a software module, a fuzzy logic module, a database, a histological database, a tissue database or a tumor database.

20

36. The method of claim 36, further comprising:
comparing an input from the sensor array to the database.

25

37. The method of claim 32, wherein the tissue type is one of a cancer, a metastatic cancer, a cyst, a tumor a coagulated tissue, an injured tissue, a lysed tissue or a necrosed tissue.

5 38. The method of claim 32, wherein the tissue property includes at least one of a physiologic property, a metabolic property, a genetic property, a thermal property, a temperature, an electrical property, an impedance, an optical property, an absorbance, a reflectance, a hemoglobin saturation, a dimensional property or a pH.

10 39. The method of claim 32, further comprising:
making a treatment decision based on information derived from a tissue identification or a tissue property.

15 40. The method of claim 32, further comprising:
making one of a diagnosis or differential diagnosis based on the tissue property.

20 41. The method of claim 32, further comprising
making a differential diagnosis based on at least two tissue properties.

25 42. The method of claim 39, wherein the treatment decision is at least one of a resection, a biopsy, an ablation, an energy delivery, an amount of energy delivery, an energy delivery duty cycle, a drug delivery, an amount of drug delivery or a chemotherapeutic agent delivery.

43. The method of claim 32, further comprising:

titrating a tissue treatment based on information derived from a tissue identification or a tissue property.

5 44. The method of claim 39, wherein the treatment is at least one of a resection, an ablation, an energy delivery, a drug delivery or a chemotherapeutic agent delivery.

10 45. The method of claim 32, wherein the tissue property includes at least one of a physiologic property, a metabolic property, a thermal property, a temperature, an electrical property, an impedance, an optical property, an absorbance, a reflectance, a dimensional property or a pH.

15 46. The method of claim 1, further comprising:
 deploying the sensor array within a selectable tissue volume.

 47. The method of claim 1, further comprising:
 obtaining a baseline tissue property measurement of the target tissue utilizing the sensor array.

20 48. The method of claim 47, further comprising:
 comparing the baseline property measurement to a second tissue property measurement made during or after the delivery of energy to the target tissue.

25 49. The method of claim 48, further comprising:
 adjusting an energy delivery parameter responsive to the comparison of the baseline measurement to the second measurement.

 50. The method of claim 49 further comprising:

adjusting the energy delivery parameter to enhance at least one of a tissue ablation time, a tissue ablation volume or a thermal injury effect.

51. The method of claim 49 further comprising:
5 adjusting the energy delivery parameter to compensate for hysteresis, thermal hysteresis, electrical hysteresis, tissue desiccation, cell lysis or protein denaturization.

52. The method of claim 49, wherein the energy delivery
10 parameter is one of a power level, a power duty cycle, a current, a fluid flow rate, or an electrolytic fluid flow rate.

53. The method of claim 48, further comprising:
15 making an treatment endpoint decision responsive to the comparison of the baseline measurement to the second measurement.

54. The method of claim 49, wherein the adjustment is
determined using logic resources coupled to the sensor array.

55. The method of claim 49, wherein the logic resources are
20 electronically coupled to a power source coupled to the energy delivery device.

56. The method of claim 49, wherein the logic resources include
25 at least one of a processor, a microprocessor, a software module, a fuzzy logic module, a database, a histological database, a tissue database or a tumor database.

57. The method of claim 1, further comprising:

deploying a marking agent; and

marking at least one of a tumor volume, a tumor surface, an ablated tissue volume, a hyperthermic tissue volume, or an injured tissue volume.

5 58. The method of claim 57, wherein tissue marking agent is one of a tumor marker, a temperature sensitive marker, a fluorescent marker, a radioactive marker, an antibody, an antibody-coupled marker, a liposome, a liposome-coupled marker, an antibody-coated liposome, a microsphere or a chemotherapeutic agent.

10

 59. The method of claim 57, wherein tissue marking agent includes a first marking agent and a second marking agent.

15 60. The method of claim 59, wherein the first marking agent is configured to mark a first tissue condition and the second marking agent is configured to mark a second tissue condition.

20 61. The method of claim 59, wherein the first marking agent is configured to mark a tumor condition and the second marking agent is configured to mark a thermal condition.

 62. The method of claim 59, wherein the first marking agent is configured to mark a first tissue temperature and the second marking agent is configured to mark a second tissue a temperature.

25

 63. The method of claim 57, wherein the marking agent is configured to enhance the delivery of energy to a least a portion of the tumor volume, the method further comprising:

enhancing the delivery of energy to at least a portion of the tumor volume.

5 64. The method of claim 63, wherein the at least a portion of the tumor volume is selectable.

 65. The method of claim 57, wherein the marking agent is configured to enhance the amount of thermal injury to a least a portion of the tumor volume, the method further comprising:
10 enhancing the thermal injury to at least a portion of the tumor volume.

 66. The method of claim 65, wherein the at least a portion of the tumor volume is selectable.
15

 67. The method of claim 57, wherein the sensor array is configured to detect a marking agent.

 68. The method of claim 67, wherein the sensor array is configured
20 to obtain one of an improved resolution or a sensitivity.

 69. The method of claim 57, further comprising
 a source of marking agent fluidically coupled to the elongated
25 delivery device, the method further comprising:
 infusing the marking agent into the target tissue site.

 70. The method of claim 57, wherein the plurality of marking agents includes a first marking agent coupled to a marking agent carrier,

wherein the marking agent carrier is configured to release the first marking at a selectable temperature, the method further comprising:

releasing the marking agent in the target tissue site at a selectable temperature.

5

71. The method of claim 70, further comprising:
delivering energy from the energy delivery device to release the marking agent.

10

72. The method of claim 70, wherein the selectable temperature is in the range of about 40° C to about 60° C.

73. The method of claim 70, wherein the selectable temperature is in the range of about 45° C to about 55° C.

15

74. The method of claim 1, wherein the geometric configuration is configured to detect one of a boundary or a volume of a tumor as at least a portion of the sensor array is advanced into a target tissue site.

20

75. The method of claim 1, wherein the energy delivery device is one of an RF electrode, a monopolar electrode or a bipolar electrode.

76. The method of claim 1, wherein a source of RF energy is coupled to the RF electrode.

25

77. The method of claim 1, wherein the sensor is one of an optical sensor, a photomultiplier, an optical fiber, a ccd, a temperature sensor or a chemical sensor.

78. The method of claim 1, wherein the geometric configuration is substantially one of a hemisphere, sphere, oval, cone, pyramidal, a polyhedron or a tetrahedron.

5 79. The method of claim 1, wherein at least one of the first or second resilient members is configured to have a changing direction of travel in tissue when advanced from the elongated delivery device to a selected tissue site.

10 80. The method of claim 79, wherein at least the first resilient member has a first direction of travel and the second resilient member has a second direction of travel.

15 81. The method of claim 79, wherein at least one of the first of the second resilient members has at least one of an elastic modulus, a bending modulus, a taper, a memory or a glass transition temperature sufficient to produce a changing direction of travel in response to a force applied by tissue.

20 82. The method of claim 1, wherein the sensor array is configured to differentiate tissue during an energy delivery interval, a tissue desiccation condition, a tissue charring condition or a tissue vaporization condition.

25 83. The method of claim 1, wherein at least one of the resilient members includes an infusion lumen and at least of the resilient members or the energy delivery device includes an infusion port, the method further comprising:

infusing a fluid into the target tissue.

5 84. The method of claim 83, wherein the fluid is one of an electrolytic solution, an electrical conductivity enhancing solution, a thermally conductivity enhancing solution, an image contrast agent, an RF energy absorption agent or an echogenic solution.

85. The method of claim 1, wherein the at least one sensor is configured to detect a change in a tissue property.

10 86. The method of claim 85, wherein the property includes at least one of a physiologic property, a metabolic property, a thermal property, a temperature, an electrical property, an impedance, an optical property, an absorbance, a reflectance, a dimensional property or a pH.

15 87. The method of claim 1, wherein the sensor array is configured to detect least one of a tissue ablation volume, a tissue thermal volume or tissue hyperthermic volume.

20 88. The method of claim 1, wherein the sensor array is configured to distinguish between cancerous and non-cancerous tissue.

25 89. The method of claim 1, wherein the at least one sensor includes a first sensor and a second sensor.

90. The method of claim 89, wherein the at least one of the first or

the second sensors are positioned at a greater distance with the respect to a longitudinal axis of the elongated delivery device than the at least one energy delivery device.

5 91. The method of claim 90, wherein the greater distance is at least one of a lateral or a longitudinal distance.

10 92. The method of claim 89, wherein at least one of the first or second sensors is an emitter, an electromagnetic emitter, an acoustical emitter, an optical emitter, a laser or an LED.

15 93. The method of claim 92, wherein the emitter is substantially positioned within a volume defined by the sensor array.

 94. The method of claim 92, wherein the emitter is substantially positioned within a volume defined by the sensor array.

20 95. The method of claim 92, wherein the emitter emits a reference signal and a probe signal.

 96. The method of claim 95, wherein the at least one sensor includes a third sensor adapted to detect the reference signal.

25 97. The method of claim 95, further comprising:
 employing the reference signal to compensate for a change in a tissue condition at the tissue site, hysteresis, thermal hysteresis, or optical hysteresis.

98. The method of claim 96, wherein the third sensor is positioned substantially adjacent or in proximity to the emitter.

5 99. The method of claim 92, wherein the emitter is configured to electromagnetic energy over a selectable frequency range.

100. The method of claim 1, wherein the sensor array includes a third and a fourth resilient member.

1000
999
998
997
996
995
994
993
992
991
990
989
988
987
986
985
984
983
982
981
980
979
978
977
976
975
974
973
972
971
970
969
968
967
966
965
964
963
962
961
960
959
958
957
956
955
954
953
952
951
950
949
948
947
946
945
944
943
942
941
940
939
938
937
936
935
934
933
932
931
930
929
928
927
926
925
924
923
922
921
920
919
918
917
916
915
914
913
912
911
910
909
908
907
906
905
904
903
902
901
900
899
898
897
896
895
894
893
892
891
890
889
888
887
886
885
884
883
882
881
880
879
878
877
876
875
874
873
872
871
870
869
868
867
866
865
864
863
862
861
860
859
858
857
856
855
854
853
852
851
850
849
848
847
846
845
844
843
842
841
840
839
838
837
836
835
834
833
832
831
830
829
828
827
826
825
824
823
822
821
820
819
818
817
816
815
814
813
812
811
810
809
808
807
806
805
804
803
802
801
800
799
798
797
796
795
794
793
792
791
790
789
788
787
786
785
784
783
782
781
780
779
778
777
776
775
774
773
772
771
770
769
768
767
766
765
764
763
762
761
760
759
758
757
756
755
754
753
752
751
750
749
748
747
746
745
744
743
742
741
740
739
738
737
736
735
734
733
732
731
730
729
728
727
726
725
724
723
722
721
720
719
718
717
716
715
714
713
712
711
710
709
708
707
706
705
704
703
702
701
700
699
698
697
696
695
694
693
692
691
690
689
688
687
686
685
684
683
682
681
680
679
678
677
676
675
674
673
672
671
670
669
668
667
666
665
664
663
662
661
660
659
658
657
656
655
654
653
652
651
650
649
648
647
646
645
644
643
642
641
640
639
638
637
636
635
634
633
632
631
630
629
628
627
626
625
624
623
622
621
620
619
618
617
616
615
614
613
612
611
610
609
608
607
606
605
604
603
602
601
600
599
598
597
596
595
594
593
592
591
590
589
588
587
586
585
584
583
582
581
580
579
578
577
576
575
574
573
572
571
570
569
568
567
566
565
564
563
562
561
560
559
558
557
556
555
554
553
552
551
550
549
548
547
546
545
544
543
542
541
540
539
538
537
536
535
534
533
532
531
530
529
528
527
526
525
524
523
522
521
520
519
518
517
516
515
514
513
512
511
510
509
508
507
506
505
504
503
502
501
500
499
498
497
496
495
494
493
492
491
490
489
488
487
486
485
484
483
482
481
480
479
478
477
476
475
474
473
472
471
470
469
468
467
466
465
464
463
462
461
460
459
458
457
456
455
454
453
452
451
450
449
448
447
446
445
444
443
442
441
440
439
438
437
436
435
434
433
432
431
430
429
428
427
426
425
424
423
422
421
420
419
418
417
416
415
414
413
412
411
410
409
408
407
406
405
404
403
402
401
400
399
398
397
396
395
394
393
392
391
390
389
388
387
386
385
384
383
382
381
380
379
378
377
376
375
374
373
372
371
370
369
368
367
366
365
364
363
362
361
360
359
358
357
356
355
354
353
352
351
350
349
348
347
346
345
344
343
342
341
340
339
338
337
336
335
334
333
332
331
330
329
328
327
326
325
324
323
322
321
320
319
318
317
316
315
314
313
312
311
310
309
308
307
306
305
304
303
302
301
300
299
298
297
296
295
294
293
292
291
290
289
288
287
286
285
284
283
282
281
280
279
278
277
276
275
274
273
272
271
270
269
268
267
266
265
264
263
262
261
260
259
258
257
256
255
254
253
252
251
250
249
248
247
246
245
244
243
242
241
240
239
238
237
236
235
234
233
232
231
230
229
228
227
226
225
224
223
222
221
220
219
218
217
216
215
214
213
212
211
210
209
208
207
206
205
204
203
202
201
200
199
198
197
196
195
194
193
192
191
190
189
188
187
186
185
184
183
182
181
180
179
178
177
176
175
174
173
172
171
170
169
168
167
166
165
164
163
162
161
160
159
158
157
156
155
154
153
152
151
150
149
148
147
146
145
144
143
142
141
140
139
138
137
136
135
134
133
132
131
130
129
128
127
126
125
124
123
122
121
120
119
118
117
116
115
114
113
112
111
110
109
108
107
106
105
104
103
102
101
100
99
98
97
96
95
94
93
92
91
90
89
88
87
86
85
84
83
82
81
80
79
78
77
76
75
74
73
72
71
70
69
68
67
66
65
64
63
62
61
60
59
58
57
56
55
54
53
52
51
50
49
48
47
46
45
44
43
42
41
40
39
38
37
36
35
34
33
32
31
30
29
28
27
26
25
24
23
22
21
20
19
18
17
16
15
14
13
12
11
10
9
8
7
6
5
4
3
2
1

101. A method of treating a tumor comprising:

providing a tissue biopsy and treatment apparatus for detecting and treating a tumor, the apparatus comprising an elongated delivery device including a lumen, the elongated delivery device being maneuverable in tissue; a sensor array deployable from the elongated member, the sensor array including a plurality of resilient members, at least one of the plurality of resilient members being positionable in the elongated delivery device in a compacted state and deployable with curvature into tissue from the elongated delivery device in a deployed state, at least one of the plurality of resilient members including at least one of a sensor, a tissue piercing distal end or a lumen, the sensor array having a geometric configuration adapted to volumetrically sample tissue at a tissue site to differentiate or identify tissue at the tissue site; and at least one energy delivery device coupled to one of the sensor array, at least one of the plurality of resilient members or the elongated delivery device;

introducing the apparatus into a target site;

maneuvering the energy delivery device through tissue responsive to information derived from the sensor array to ablate a tumor volume;

delivering energy from the energy delivery device to ablate or necrose at least a portion of the tumor volume; and

determining an amount of tumor volume ablation utilizing the sensor array.

102. A method of treating a tumor comprising:

providing a tissue biopsy and treatment apparatus for detecting and treating a tumor, the apparatus having a sensor array positionable at a target tissue site, the sensor array including at least a first and a second resilient member, at least one of the first or second resilient members including at

least one of a a sensor, a lumen, a sensor member positionable in the lumen,
an energy delivery or a tissue piercing distal end;

introducing the apparatus into the target tissue site;

positioning the sensor array at the target tissue site;

5 utilizing the sensor array to make a first measurement of a tissue
parameter at the target site or retrieving a tissue parameter for the target site
from a database of tissue parameters;

delivery energy to the target tissue site;

10 utilizing the sensor array to make a second measurement of the
tissue parameter during or after an energy delivery interval;

comparing one of the first measurement or the retrieved parameter to
the second measurement; and

15 determining an amount of injury or ablation of the target tissue
volume utilizing a comparison between one of the first measurement or the
retrieved parameter to the second measurement.

103. The method of claim 102, further comprising:
determining a treatment endpoint.

20 104. A method of treating a tumor comprising:
providing a tissue biopsy and treatment apparatus for detecting and
treating a tumor, the apparatus comprising an elongated delivery device
including a lumen, the elongated delivery device being maneuverable in
tissue; a sensor array deployable from the elongated member, the sensor
25 array including a plurality of resilient members, at least one of the plurality
of resilient members being positionable in the elongated delivery device in a
compacted state and deployable with curvature into tissue from the
elongated delivery device in a deployed state, at least one of the plurality of
resilient members including at least one of a sensor, a tissue piercing distal

end or a lumen, the sensor array having a geometric configuration adapted to volumetrically sample tissue at a tissue site to differentiate or identify tissue at the tissue site; and at least one energy delivery device coupled to one of the sensor array, at least one of the plurality of resilient members or the elongated delivery device;

5 distinguishing a tissue type utilizing the sensor array means;

positioning the energy delivery device means utilizing tissue type information derived from the sensor array means to ablate a tumor volume;

delivering energy from the energy delivery device to ablate or

10 necrose at least a portion of the tumor volume; and

determining an amount of tumor volume ablation utilizing the sensor array.